



MJ-9120

Omnidirectional Barcode Scanner



MJ9120 best-selling hand-free omnidirectional barcode scanner presents an innovative, elegant and affordable solution to retail applications where counter space is at a premium.

Features

- Omnidirectional and 20 lines optical grating mode: No need accurate positioning
- Multiple interface: Through Multiple interface to protect your hardware investment
- Common cable: Easier to replace and upgrade
- Mini size: Suitable for the narrow environment of cash counter.
- Adjustable stand: For comfortable use and high efficiency
- Anti-shock(built-in): To protect scanning module and improving durability
- Full-automatic mode

Replaceable cables for PowerLink users

Fixed on the wall or check counter

Customize the depth-of-field according to different circumstance

Edit the barcode data to meet the requirements of the users

Multiple beeper tones

Operate Parameter		Physical parameter	
Light Source	675nm±10nm laser	Height	150mm
Power	0.681W	Width	Base: 125mm Laser head: 90mm
Scan Depth	0mm-215mm	Depth	110mm
Scan width	60mm @ face; 105mm @ 216mm	Weight	350g
Scan rate	1200 scan/sec	Cable	Standard 2.1m Straight, 2.7m Straight for choice
Resolution	5.2 mil	Electrical parameter	
Scanning lines	20 lines	Voltage	5VDC±0.25V
Scanning mode	5 group 4 parallel lines	Power	1.1W typical @ 5VDC
Interface	Rs232 , PC Keyboard Wedge , Light Pen Emulation , Stand-Alone Keyboard , OCIA, IBM 468X/469X	Quiescent current	120mA typical @ 5VDC
		Working current	220mA
Contrast	35% minimum	DC power	Class 2; 5.0VDC @ 650mA
Reading characters capability	Maximum 80 characters	Laser level	CDRH; Class II ; EN60825-1; 1994/A11; 1996Class1
		EMC	FCC ClassB
Scanning angle	Tilt 360°,Elevation 60°,oblique 60°	Environment	
Buzzer	7 mode or mute	Working temperature	0°C to 40°C
Indicator status	Green=preparing to scan , Red=Scan and decode successfully	Storage temperature	-40°C to -60°C
		Humidity	5% to 95%(non-condensing)